

Versalite™ skylight system— high performance, ready-to-install skylights

The Versalite fully guttered framing system is **shipped fully assembled and pre-glazed**, ready to install on your curb.

Standard glazing options include insulating glass units, multi-wall polycarbonate panels and translucent fiberglass panels. The Versalite skylight system features a **patented glazing clip** which creates a thermal break between the one-piece glazing caps and the framing members and provides for uniform compression on the glazing material using EPDM gaskets. The perimeter framing is also thermally broken to provide **maximum energy performance** and reduce condensation.



Versalite Features

- Integral condensation gutters on all framing members
- One piece glazing caps-no exposed fasteners
- Dry glazed system requires no sealant
- Available painted in Kynar® 500/Hylar® 5000 finish or anodized finish
- Shipped pre-glazed and pre-assembled
- Lean 2, Ridge, Pyramid, Octagon and Hip-Ridge available
- Available up to 8' square, up to 8' wide by unlimited length, octagon and now in Lean 2 in multiple pitches

VersaCurb Features

- Galvanized curb wall with insulation and treated 2 x 4 wood nailer
- Curb is fully assembled, ready to install
- Appropriate for Versalite units designed for loads up to 40psf (consult factory if loads to exceed 40psf)
- Galvanized steel construction



Finishes

Finish options include clear and bronze anodized ready to ship 6 weeks after release for production. Kynar® 500 Hylar® 5000 paint, color to be selected from our standard color chart featuring 20 standard colors, will be ready to ship 8 weeks after release for production.

Tested Performance

Static Air Infiltration @ 6.24 psf per ASTM E283-91

Allowable: .5 CFM/FT

Tested: .1 CFM/FT

Result: Pass

Static Water Infiltration @ 15.0 psf per ASTM E331-93

Allowable: No Uncontrolled Water

Tested: No Uncontrolled Water

Result: Pass

Options

VLG: (insulating glass; Low-E optional); clear HS/clear laminated; green HS/clear laminated; bronze HS/clear laminated; grey HS/clear laminated; Call for special glass

VLP: (multiwall polycarbonate); clear multiwall; white multiwall

VLT: (fiberglass, translucent panel); crystal/crystal; crystal/white

	VLG	VLP	VLT
Impact Resistant	Good	Best	Better
Light Transmission	Best	Good	Better
Shading Coefficient	Best	Good	Better
Light Distribution	Good	Better	Best
Durability	Best	Better	Good
Value	Best	Good	Better

KYNAR 500® is a registered trademark of Atofina
 HYLAR 5000® is a registered trademark of Ausimont USA, Inc.